EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	20	(((call adj type) with rout$4) with ((destination adj address) or number or url or uri or urn)).ab,bsum.	US-PGPUB; USPAT	OR	ON	2008/11/14 06:56
L2	6	(single adj (address or identifier)) with device with subscriber	US-PGPUB; USPAT	OR	ON	2008/11/14 06:56
L3	50	(single adj (address or identifier)) with subscriber	US-PGPUB; USPAT	OR	ON	2008/11/14 06:56
L4	54	(single adj (address or identifier)) with (subscriber or user) with device	US-PGPUB; USPAT	OR	ON	2008/11/14 06:56
L5	6	(determin$4 or detect$4 or learn$4 or identif$4) with (call adj type) with (media adj type)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2008/11/14 06:56
L6	5	((determin$4 or detect$4 or learn$4 or identif$4) with (call adj type)) same (media adj type) same (protocol or sip or isup)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2008/11/14 06:56
L7	9	((determin$4 or detect$4 or learn$4 or identif$4) with (call adj type)) same (media adj type)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2008/11/14 06:56
L8	23	(call adj type) same (media adj type)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2008/11/14 06:56
L9	9	sip same isup same ((call or media) adj type)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2008/11/14 06:56

| L10 | 44 | (((call or media) adj type) with sip with protocol) and (@ad<"20040419" or @rlad<"20040419") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2008/11/14 06:56 |
| L11 | 23 | (L1 L2 L3 L4 L5 L6 L7 L8 L9 L10) and (@pd>"20080131") | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2008/11/14 06:56 |

11/14/08 7:06:47 AM
C:\Documents and Settings\rscheibel\My Documents\EAST\Workspaces\10827039 - system and method for routing calls in a wireless network using a single point of contact.wsp